


## STRAIGHT ADAPTORS

### ML-ML

MET LIGHT MALE X MET LIGHT MALE  
METRIC 24° CONE LIGHT MALE X METRIC 24°  
CONE LIGHT MALE STRAIGHT

- ISO 8434-1



| Part Number | Metric Male Thread | suits tube | L1 - mm | L2 - mm | Hex A/F (CH1) | Hex A/F (CH2) | PN (bar) |
|-------------|--------------------|------------|---------|---------|---------------|---------------|----------|
| ML-ML-1212  | M12-1.5            | 6          | 24      | 10      | 12            | 14            | 500      |
| ML-ML-1414  | M14-1.5            | 8          | 25      | 11      | 14            | 17            | 500      |
| ML-ML-1616  | M16-1.5            | 10         | 27      | 13      | 17            | 19            | 500      |
| ML-ML-1818  | M18-1.5            | 12         | 28      | 14      | 19            | 22            | 400      |
| ML-ML-2222  | M22-1.5            | 15         | 30      | 16      | 24            | 27            | 400      |
| ML-ML-2626  | M26-1.5            | 18         | 31      | 16      | 27            | 32            | 400      |
| ML-ML-3030  | M30-2              | 22         | 35      | 20      | 32            | 36            | 250      |
| ML-ML-3636  | M36-2              | 28         | 36      | 21      | 41            | 41            | 250      |
| ML-ML-4545  | M45-2              | 35         | 41      | 20      | 46            | 50            | 250      |
| ML-ML-5252  | M52-2              | 42         | 43      | 21      | 55            | 60            | 250      |