


## STRAIGHT ADAPTORS

### UL-UL

MET LIGHT FEMALE X MET LIGHT FEMALE  
 METRIC 24° CONE LIGHT FEMALE SWIVEL NUT X  
 METRIC 24° CONE LIGHT FEMALE SWIVEL NUT  
 STRAIGHT



Part Number	Metric Female Thread - m D2	Metric Female Thread - m D1	D2 - mm	D1 - mm	L1-mm	Hex A/F (CH1)	Hex A/F (CH2)	PN (bar)
UL-UL-1212	M12-1.5	M12-1.5	6	6	40	14	14	500
UL-UL-1214	M12-1.5	M14-1.5	6	8	37	17	14	500
UL-UL-1414	M14-1.5	M14-1.5	8	8	40	17	17	500
UL-UL-1416	M14-1.5	M16-1.5	8	10	37	19	17	500
UL-UL-1616	M16-1.5	M16-1.5	10	10	40	19	19	500
UL-UL-1618	M16-1.5	M18-1.5	10	12	36	22	19	400
UL-UL-1622	M16-1.5	M22-1.5	10	15	40	27	19	400
UL-UL-1818	M18-1.5	M18-1.5	12	12	40	22	22	400
UL-UL-1822	M18-1.5	M22-1.5	12	15	40	27	22	400
UL-UL-1826	M18-1.5	M26-1.5	12	18	40	34	22	400
UL-UL-2222	M22-1.5	M22-1.5	15	15	44	27	27	400
UL-UL-2226	M22-1.5	M26-1.5	15	18	44	32	27	400
UL-UL-2626	M26-1.5	M26-1.5	18	18	43	32	32	400
UL-UL-2630	M26-1.5	M30-2	18	22	46	36	32	250
UL-UL-2636	M26-1.5	M36-2	18	28	47	41	32	250
UL-UL-3030	M30-2	M30-2	22	22	50	36	36	250
UL-UL-3036	M30-2	M36-2	22	28	50	41	36	250
UL-UL-3636	M36-2	M36-2	28	28	51	41	41	250