


STANDARD SERIES

QBHNV

BRASS POPPET SEAL

INTERCHANGE ACCORDING TO ISO 7241-1 PART B

- Please enquire for other combinations of base size and thread form.
- Overall length when connected is calculated based on both couplings having the same thread form and size.
- Recommended for: Industrial or chemical applications.
- Connection: Connect without pressure - pull back female sleeve and push couplings to connect. Disconnect under pressure not allowed - pull back female sleeve to disconnect.
- Latching: Balls latching.
- Shut-off system: Poppet valve. Guidevalve with mechanical backstop.
- Temperature range: -25°C to +125°C
- Standards: Interchangeability according to ISO 7241-1 part B
Interchangeability with all QHNV and SQHNV series couplings.



Part Number	Base Size	Threadform	Thread Size	Coupling Length - L1	Coupling O.D - D1	Hex Size A/F (Hex 1)
QBHNV-F02	02	BSPPF socket	1/8-28	50.0	23	18
QBHNV-F04	04	BSPPF socket	1/4-19	56.0	28	19
QBHNV-F06	06	BSPPF socket	3/8-19	64.0	35	24
QBHNV-F08	08	BSPPF socket	1/2-14	71.5	44	30
QBHNV-F12	12	BSPPF socket	3/4-14	89.0	52	36
QBHNV-M02	02	BSPPF socket	1/8-27	31.5	18	16
QBHNV-M04	04	BSPPF socket	1/4-19	35.0	21	19
QBHNV-M06	06	BSPPF socket	3/8-19	39.0	24.5	22
QBHNV-M08	08	BSPPF socket	1/2-14	44.0	30	27
QBHNV-M12	12	BSPPF socket	3/4-14	55.0	38	34