


## SCREW LOCK SERIES

### QPVV

#### HYDRAULIC TOOL COUPLINGS

#### INTERCHANGE WITH EUROPE AND US MARKETS

- QPVV series are only available in base sizes 04 and 06 (1/4 and 3/8).
- Please enquire for further thread forms and sizes.
- Connection: Connect with pressure - screw couplings together to connect.
- Disconnect with pressure - unscrew couplings to disconnect.
- NOTE: Can be connected with pressure in either or both couplings.
- Latching: Threaded with safety lock.
- Shut-off system: Poppet valve. Interchanges with ball-type hydraulic tool couplings.
- Temperature range: -25°C to +125°C
- Standards: Faster proprietary standard; interchange with US and European hydraulic tool couplings.



| Part Number | Base Size | Threadform     | Thread Size | Coupling Length - L1 | Coupling O.D - D1 | Hex Size A/F (Hex 1) |
|-------------|-----------|----------------|-------------|----------------------|-------------------|----------------------|
| QPVV-F04L   | 04        | NPTF male boss | 1/4-18      | 63                   | 33                | 21                   |
| QPVV-F06L   | 06        | NPTF male boss | 3/8 - 18    | 83                   | 36                | 25                   |
| QPVV-M04AC  | 04        | NPTFF socket   | 1/4-18      | 63                   | 30                | 27                   |
| QPVV-M06AC  | 06        | NPTFF socket   | 3/8-18      | 83                   | 35                | 32                   |