


SCREW LOCK SERIES

QVVS

DUAL LOCK

FASTER PROPRIETARY STANDARD

- Sizes above 20 (1.1/4) are available on request.
- Please enquire for other combinations of base size and thread form.
- Overall length when connected is calculated based on both couplings having the same thread form and size.
- Recommended for: Construction, earthmoving, hydraulic tools.
- Connection: Connect with pressure - screw couplings together to connect. Disconnect with pressure - unscrew couplings to disconnect.
- NOTE: Can be connected with pressure in either or both couplings.
- Latching: Threaded.
- Shut-off system: Poppet valve. Reinforced guidevalve with mechanical backstop.
- Temperature range: -25°C to +125°C
- Standards: Faster proprietary standard. Interchangeability with all QVV series couplings to size 16 (1).



Part Number	Base Size	Threadform	Thread Size	Coupling Length - L1	Coupling O/D - D1	Hex Size A/F (Hex 1)	Inner Coupling O.D - D3
QVVS-F20	20	BSPPF socket	1.1/4-11	123.0	80	65	
QVVS-M04	04	BSPPF socket	1/4-19	43.0	28	25	14.1
QVVS-M06	06	BSPPF socket	3/8-19	48.0	35	30	18.9
QVVS-M08	08	BSPPF socket	1/2-14	53.0	38	34	20.5
QVVS-M12	12	BSPPF socket	3/4-14	63.0	50	46	27.9
QVVS-M16	16	BSPPF socket	1-11	72.0	55	50	31.3
QVVS-M20	20	BSPPF socket	1.1/4-11	86.0	70	65	43.9
QVVS-F04	04	BSPPF socket	1/4-19	58.0	30	22	
QVVS-F06	06	BSPPF socket	3/8-19	62.0	40	30	
QVVS-F08	08	BSPPF socket	1/2-14	71.0	45	34	
QVVS-F12	12	BSPPF socket	3/4-14	63.0	55	41	
QVVS-F16	16	BSPPF socket	1-11	100.0	60	50	