Hydraulink

ENDURO MULTISPIRAL HOSE

ENDURO6000

ENDURO ST COVER - FOUR/SIX SPIRAL WIRE HOSE
SPIRALLED WIRE REINFORCED HOSE - SAE 100
R15 - MILLION IMPULSE CYCLES



- Comes with SuperTuff (ST) cover for increased protection against abrasion in severe operating environments
- Recommended for: Extremely high pressure and high impulse hydraulic applications.
- Internal tube: Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB,HFC) and bio-degradable hydraulic fluids.
- Reinforcement: Four (six for -24) alternating layers of spiralled, high tensile steel wires.
- External cover: Weather & abrasion resistant synthetic rubber. MSHA approved.
- Temperature range: -40°C to +121°C
- Standards: ISO 18752-CC, Exceeds SAE 100 R15.
- Characteristics: Extra flexible, up to 1/2 SAE bend radius

Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - Inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
ENDURO6000-06	06	10	3/8	20.2	6100	420	24400	1680	65
ENDURO6000-08	08	12	1/2	22.9	6100	420	24400	1680	90
ENDURO6000-10	10	16	5/8	26.5	6100	420	24400	1680	100
ENDURO6000-12	12	19	3/4	30.5	6100	420	24400	1680	120
ENDURO6000-16	16	25	1	37.5	6100	420	24400	1680	150
ENDURO6000-20	20	32	1 1/4	47.3	6100	420	24400	1680	400
ENDURO6000-24	24	38	1 1/2	57.4	6100	420	24400	1680	460

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.