

PETROLEUM HOSE

REPD01

MAXIMUS R6 PUSH-ON RUBBER PUSH-ON - BLACK

- Conforming Standards: SAE J517; SAE 100R6
- Temperature: -40°C to +100°C for air +71°C
- Cover: Black; Smooth Extruded Rubber Compound
- Tube: Black; Smooth Extruded Nitrile Rubber Compound
- Reinforcement: High Strength Synthetic Cord
- Applications: Recommended For Petroleum Based Hydraulics Oils/Water Glycol Antifreeze Solutions/Hot Lubricating Oils/Air. Not recommended for gasoline or diesel fuels. Cover is oil and abrasion resistant.

| Part Number | Size | Hose I.D (mm) | Hose O.D (mm) | WP (psi) | BP (psi) | Weight kg/mtr |
|-------------|------|---------------|---------------|----------|----------|---------------|
| REPD01-005 | 5 | 4.8 | 11 | 525 | 2100 | 0.17 |
| REPD01-006 | 6 | 6.3 | 12 | 425 | 1680 | 0.19 |
| REPD01-008 | 8 | 7.9 | 14 | 425 | 1680 | 0.23 |
| REPD01-010 | 10 | 9.5 | 16 | 425 | 1680 | 0.24 |
| REPD01-012 | 12 | 12.7 | 20 | 425 | 1680 | 0.33 |
| REPD01-016 | 16 | 15.9 | 23 | 425 | 1680 | 0.40 |
| REPD01-019 | 19 | 19.1 | 27 | 315 | 1280 | 0.51 |