

AIR & WATER

RWWD23

ETNA

RUBBER MARINE WET EXHAUST

- Approved By Lloyds; Certificate 99/00169 (EZ)
- Temperature: -30°C to +100°C
- Cover: Black; Corrugated Wrapped Finish Cr Flame Retardant Rubber Compound
- Tube: Black; Cr Rubber Compound
- Reinforcement: High Strength Synthetic Cord Plus Embedded Steel Helix Wire
- Applications: Hardwall Hose specially designed for the marine industry for conveying wet exhaust fumes from the engine intake and bilge exhaust. Also; Due to Unique Sizes; Can Be Used In Industrial Applications.

Part Number	Size	Hose I.D (mm)	Min Bend Radius (mm)	WP (psi)	BP (psi)	Weight kg/mtr
RWWD23-025	25	25.4	110	25	75	0.48
RWWD23-032	32	32.1	130	25	75	0.65
RWWD23-038	38	38.1	150	25	75	0.75
RWWD23-045	45	44.5	170	25	75	0.87
RWWD23-051	51	50.8	180	25	75	1.07
RWWD23-063	63	63.5	200	25	75	1.30
RWWD23-076	76	76.1	250	25	75	1.46
RWWD23-090	90	88.9	330	25	75	1.73
RWWD23-102	102	101.6	410	25	75	2.06
RWWD23-127	127	127	560	25	75	2.58
RWWD23-152	152	152.6	680	25	75	3.18