Hydraulink

HYDRAULIC

OIL ISO 68

ISO GRADE 68 HYDRAULIC OIL



- Performance Standards: ISO 11158 category HM
- ISO 6743-4 category HM
- ANFOR NFE 48 603 HM
- ANFOR NFE 48-691 (wet)
- SS155434
- SEB 181 222
- VDMA 24318
- DIN 51 524 part 2 HLP
- CINCINNATI MILACRON P 70
- DENISON HF-0, HF-1, HF-2
- VICKERS I-286-S, M-2950-S
- ASTM D 6158
- US Steel 126, 136, 127
- RACINE variable volume vane pumps
- Commercial Hydraulics
- Eaton Brochure 03-401-2010
- Description: Blended from high-quality mineral oils possessing a high viscosity index and low pour point giving long and trouble free service life and will be chemically stable under severe operating conditions. Can be used for all types of hydraulic systems, verins working in very severe conditions. Construction machinery, agricultural machinery and in the industrial sector. Suitable for all types of pumps: Axial pistons, radial pistons, gear systems, blades. Formulated using paraffinic, high viscosity index mineral oil, augmented with performance additives including a zinc anti-wear treatment.

Part Number	Size (Litre)
OIL ISO 68 18L	18
OIL ISO 68 200L	200

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.