Hydraulink

HYDRAULIC

MOTULTECH RUBRIC BIO 46

ISO GRADE 46 HYDRAULIC OIL
BIODEGRADABLE



- Performance Standards: ISO 6743-4
- ISO 15380
- DIN 51524 Part 2
- DIN 51524 Part 3
- Approvals: European Ecolabel under N° DE/027/027
- Ecolabel Blaue Engel under rubric N° RAL-UZ 178
- Bosch Rexroth under number RE 90221-01
- Waste code AW 130112
- Properties & Advantages: Very fluid at low temperatures allowing easy start up.
- Excellent shear resistance allowing use at very high pressure.
- Excellent anti-wear properties which increase the pumps life.
- Harmless to elastomers.
- High biodegradability level >90% in 21 days.
- High resistance to oxidation: Long drain oil.
- Anti-corrosion, Anti-rust, Anti-foam.
- Applications: Motul Rubric BIO 46 is a 100% synthetic biodegradable hydraulic oil using high performance Esters. Specially developed for all hydraulic systems working in severe conditions, operating at high pressure within important temperature variation and requiring an environmentally friendly Ecolabel lubricant.

Part Number	Size (KG)
100436	190
104418	20

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.