

HIGH PRESSURE HOSE

G2XH

HIGH TEMP. TWO WIRE BRAID HOSE
BRAIDED WIRE REINFORCED HOSE - SAE 100R2
Type S



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: High temperature, high pressure hydraulic applications
- Internal tube: CPE based.
- Reinforcement: Two braids of high tensile steel wire.
- External cover: CSM based. MSHA approved. Blue.
- Temperature range: -40°C to +150°C.
- Standards: EN 853 2SN. SAE 100R2S - high temperature. ISO 1436.
- Characteristics: G2XH hose is compatible with biodegradable hydraulic fluids like synthetic esters, and vegetable oils as well as petroleum-based fluids.

Part Number	Internal Size	Internal DN	Internal Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
4G2XH	04	6	1/4	15.0	6000	420	24000	1680	100
6G2XH	06	10	3/8	18.8	5000	350	20000	1400	130
8G2XH	08	12	1/2	21.8	4250	290	17000	1160	180
10G2XH	10	16	5/8	24.9	3625	250	14500	1000	200
12G2XH	12	19	3/4	29.0	3100	215	12400	860	240
16G2XH	16	25	1	37.6	2500	170	10000	680	300