

LOW PRESSURE HOSE

LOL

PUSH-LOCK FIBRE BRAID HOSE BRAIDED FIBRE REINFORCED HOSE



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: Petroleum-based hydraulic oils, antifreeze solutions, water, hot lubricating oils and air. Suitable for low-pressure cleaning and pneumatic systems, return lines and low pressure lines. Push-Lock hose and couplings are not recommended for pressure surge applications or critical applications.
- Internal tube: Nitrile based.
- Reinforcement: One fibre braid.
- External cover: Oil and abrasion resistant synthetic rubber (blended nitrile). MSHA approved.
- Temperature range: -40°C to +100°C constant and +121°C intermittent.
- Standards: Gates proprietary.
- Characteristics: Available in 6 colours for easy colour coding. Easy to assemble.
- Suffix A = black, B = blue, C = grey, G = green, R = red, Y = yellow. Please note some size/colour combinations are not held in inventory and are subject to minimum order requirements.

Part Number	Colour	Internal Size	Internal Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
3LOLA	Black	03	3/16	10.4	300	21	1200	84	75
4LOLA	Black	04	1/4	11.9	300	21	1200	84	75
4LOLB	Blue	04	1/4	11.9	300	21	1200	84	75
4LOLY	Yellow	04	1/4	11.9	300	21	1200	84	75
5LOLA	Black	05	5/16	14.0	300	21	1200	84	75
6LOLA	Black	06	3/8	15.9	300	21	1200	84	75
6LOLB	Blue	06	3/8	15.9	300	21	1200	84	75
6LOLC	Grey	06	3/8	15.9	300	21	1200	84	75
6LOLG	Green	06	3/8	15.9	300	21	1200	84	75
6LOLR	Red	06	3/8	15.9	300	21	1200	84	75
6LOLY	Yellow	06	3/8	15.9	300	21	1200	84	75
8LOLA	Black	08	1/2	19.6	300	21	1200	84	130
8LOLB	Blue	08	1/2	19.6	300	21	1200	84	130
10LOLA	Black	10	5/8	23.9	300	21	1200	84	150
10LOLB	Blue	10	5/8	23.9	300	21	1200	84	150
12LOLA	Black	12	3/4	26.9	300	21	1200	84	180
12LOLB	Blue	12	3/4	26.9	300	21	1200	84	180