

EXTREMELY HIGH PRESSURE HOSE

EFG4K

FOUR SPIRAL WIRE HOSE

SPIRAL WIRE REINFORCED HOSE - SAE 100R12



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: Extremely high pressure and high impulse hydraulic applications.
- Internal tube: Nitrile based.
- Reinforcement: Four alternating layers of spiralled, high tensile steel wire.
- External cover: Neoprene based, MSHA approved.
- Temperature range: -40°C to +121°C
- Standards: Gates proprietary. EN 856 R12. SAE 100R12. Meets or exceeds performance requirements of EN 856 4SP (-16, -20).
- Characteristics: Extremely flexible. Compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids in sizes -06 to -20 (not -24)

Part Number	Internal Size	Internal DN	Internal Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
6EFG4K	06	10	3/8	20.5	4000	280	16000	1120	65
8EFG4K	08	12	1/2	24.0	4000	280	16000	1120	90
10EFG4K	10	16	5/8	27.6	4000	280	16000	1120	100
12EFG4K	12	19	3/4	30.7	4000	280	16000	1120	120
16EFG4K	16	25	1	38.0	4000	280	16000	1120	150
20EFG4K	20	31	1.1/4	47.0	4000	280	16000	1120	210