



**SCREW LOCK SERIES**



**DUAL LOCK  
QVVS - TECHNICAL  
DATA**  
Page 15-1

**SCREW LOCK SERIES**
**QVVS - TECHNICAL DATA**
**DUAL LOCK**
**FASTER PROPRIETARY STANDARD**
**Pressure Drop**

 Data shown in the diagram are indicative and not binding.  
 (1) 1 MPa = 10 bar  
 Dash-dot are specified.


Part Number	Rated Flow (l/min)	Maximum WP Connected - bar	Maximum WP Connected - psi	Minimum BP Disconnected - psi	Minimum BP Connected - psi	Fluid Spill - ml max
QVVS-F04	8	800	11600	34800	36250	1
QVVS-M04	8	800	11600	34800	36250	1
QVVS-F06	18	760	11020	36250	33350	1.5
QVVS-M06	18	760	11020	42050	33350	1.5
QVVS-F08	30	730	10585	31900	31900	2
QVVS-M08	30	730	10585	34510	31900	2
QVVS-F12	45	700	10150	33350	31030	3
QVVS-M12	45	700	10150	30740	31030	3
QVVS-F16	90	530	7685	32480	28130	10
QVVS-M16	90	530	7685	23200	28130	10
QVVS-F20	140	600	8700	26100	29000	15
QVVS-M20	140	600	8700	26100	29000	15

† - Please contact Hydraulink for further details and availability.

Pricing current as at 17 Jul 2019 and excludes GST. Hydraulink reserve the right to change pricing and technical specifications without notice.